

Pietra

The Pietra Range is a sophisticated poreclain tile collection that captures the timeless elegance of natural stone, combining durability with effortless style across a wide variety of spaces. Inspired by the organic movement and subtle veining of natural stone, Pietra delivers a refined, contemporary aesthetic suitable for both residential and commercial interiors.

Designed for versatility, the range is available in an extensive selection of formats including Chevron, Square mosaics, Subway (50x300mm), 300x300mm, 300x600mm, 600x600mm, and 600x1200mm. This comprehensive format offering allows for seamless floor-to-wall applications, feature walls, splashbacks, and detailed design elements enabling cohesive, large-scale installations or intricate statement areas within the same colour palette.


Pietra is available in nine timeless colourways: White, Cream, Ivory, Beige, Terra, Silver, Grisio, Antecite and Black. From warm neutrals and earthy tones to cool greys and bold charcoals, the palette has been carefully curated to suit classic, contemporary, and architectural interiors alike. Combining natural beauty with low-maintenance practicality and high-performance ceramic durability, the Pietra Range is ideal for creating elegant, continuous surfaces that enhance bathrooms, kitchens, living areas, and commercial environments with understated sophistication.

PIETRA

COLOURS, FORMATS & FINISHES

Coming soon					Coming soon				
WhiteCreamIvoryBeigeTerraSilverGrigioAntraciteBlack									
Matt P3									
600 x 1200mm									
600 x 600mm									
300 x 600mm									
300 x 300mm									
260 x 300mm Chevron									
50 x 300mm									
50 x 50mm Mosaic									
Textured P5									
600 x 600mm									


White



600 x 600mm
PIETWH60 (matt)
PIETWH60T (textured)




600 x 1200mm
PIETWH612 (matt)



50 x 300mm
PIETWH530 (matt)




Chevron Mosaic
PIETWHCV (matt)



Square Mosaic
PIETWHX (matt)




300 x 300mm
PIETWH30 (matt)




300 x 600mm
PIETWH36 (matt)


Cream



600 x 600mm
PIETCR60 (matt)
PIETCR60T (textured)



600 x 1200mm
PIETCR612 (matt)



50 x 300mm
PIETCR530 (matt)




Chevron Mosaic
PIETCRCV (matt)




Square Mosaic
PIETCRX (matt)



300 x 300mm
PIETCR30 (matt)




300 x 600mm
PIETCR36 (matt)



Ivory

V2
P3 P5



600 x 600mm
PIETIV60 (matt)
PIETIV60T (textured)



600 x 1200mm
PIETIV612 (Matt)



50 x 300mm
PIETIV530 (matt)




Chevron Mosaic
PIETIVCV (matt)



Square Mosaic
PIETIVX (matt)



300 x 300mm
PIETIV30 (matt)



300 x 600mm
PIETIV36 (matt)



Beige

V2
P3 P5



600 x 600mm
PIETBE60 (matt)
PIETBE60T (textured)



600 x 1200mm
PIETBE612 (matt)



50 x 300mm
PIETBE530 (matt)




Chevron Mosaic
PIETBECV (matt)




Square Mosaic
PIETBEX (matt)



300 x 300mm
PIETBE30 (matt)



300 x 600mm
PIETBE36 (matt)



600 x 600mm
PIETTE60 (matt)
PIETTE60T (textured)



600 x 1200mm
PIETTE612 (matt)



50 x 300mm
PIETTE530 (matt)




Chevron Mosaic
PIETTECV (matt)



Square Mosaic
PIETTEX (matt)



300 x 300mm
PIETTE30 (matt)



300 x 600mm
PIETTE36 (matt)



600 x 600mm
PIETSIL60 (matt)
PIETSIL60T (textured)




600 x 1200mm
PIETSIL612 (matt)



50 x 300mm
PIETSIL530 (matt)




Chevron Mosaic
PIETSILCV (matt)



Square Mosaic
PIETSILX (matt)



300 x 300mm
PIETSIL30 (matt)



300 x 600mm
PIETSIL36 (matt)



Grigio



600 x 600mm
PIETGR60 (matt)
PIETGR60T (textured)




600 x 1200mm
PIETGR612 (matt)



50 x 300mm
PIETGR530 (matt)



Chevron Mosaic
PIETGRCV (matt)




Square Mosaic
PIETGRX (matt)



300 x 300mm
PIETGR30 (matt)



300 x 600mm
PIETGR36 (matt)



Antracite




600 x 600mm
PIETAT60 (matt)
PIETAT60T (textured)




600 x 1200mm
PIETAT612 (matt)



50 x 300mm
PIETAT530 (matt)




Chevron Mosaic
PIETATCV (matt)




Square Mosaic
PIETATX (matt)



300 x 300mm
PIETAT30 (matt)



300 x 600mm
PIETAT36 (matt)



600 x 600mm
PIETBK60 (matt)
PIETBK60T (textured)




600 x 1200mm
PIETBK612 (matt)




50 x 300mm
PIETBK530 (matt)




Chevron Mosaic
PIETBKCV (matt)



Square Mosaic
PIETBKX (matt)



300 x 300mm
PIETBK30 (matt)



300 x 600mm
PIETBK36 (matt)



Technical Specifications

Properties	Test Method	Required Value	Value	Applies to
 Water absorption	EN ISO 10545-3	$\leq 0.5\%$	<3%	Full range
 Determination of dimensions	EN ISO 10545-2	Length and width $\pm 0.6\%$ Thickness $\pm 5.00\%$ Transmutation $\pm 0.5\%$	Length and width $\pm 0.6\%$ Thickness $\pm 5.00\%$ Transmutation $\pm 0.1\%$	Full range
 Breaking strength	EN ISO 10545-4	≥ 1100 N	≥ 1606 N	Full range
 Modulus of rupture	EN ISO 10545-4	≥ 35 N/mm ²	≥ 37.3 N/mm ²	Full range
 Abrasion resistance	EN ISO 10545-7	≤ 205 mm ²	≤ 160 mm ²	Full range
 Slip resistance (wet pendulum test)	AS 4586-2013/ AMDT1-2017	N/A	P3 - Matt P5 - Textured	Matt, Textured
 Chemical resistance	EN ISO 10545-13	Min. GB	Class 5	Full range
 Stain resistance	ISO 10545-14	Min class 3	Class 5	Full range
 Origin	N/A	N/A	China	Full range
 Shade variation	N/A	N/A	V3	Full range



Packing Information

Tile Description		Quantity per Box	Quantity per m2		Quantity per Pallet	
Size (mm)	Finish	Pieces	Pieces	Weight	m2	Boxes
Square Mosaic	Matt	11	-	1.80kg	-	-
Chevron Mosaic 260 x 300	Matt	11	-	1.60kg	-	-
50 x 300	Matt	40	66.67	20.00kg	64.80	108
300 x 300	Matt	11	11.11	20.14kg	55.44	56
300 x 600	Matt	8	5.56	22.22kg	57.60	40
600 x 600	Matt Textured	4	2.78	20.50kg	57.60	40
600 x 1200	Matt	2	1.39	22.22kg	46.08	32



The data and information contained in these specification sheets are indicative only unless stated otherwise. As Japan Ceramics cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation. The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose. To the maximum extent permitted by law, ColorTile will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.

Technical Specification

	Properties	Test Method	Required Value	Value	Applies to
	Water absorption	EN ISO 10545-3	$\leq 0.5\%$	$\leq 0.5\% < 3\%$	Full range
	Determination of dimensions	EN ISO 10545-2	Length and width $\pm 0.6\%$ Thickness $\pm 5.00\%$ Transmutation $\pm 0.5\%$	Length and width $\pm 0.6\%$ Thickness $\pm 5.00\%$ Transmutation $\pm 0.1\%$	Full range
	Breaking strength	EN ISO 10545-4	≥ 1100 N	≥ 1606 N	Full range
	Modulus of rupture	EN ISO 10545-4	≥ 35 N/mm ²	≥ 37.3 N/mm ²	Full range
	Abrasion resistance	EN ISO 10545-7	≤ 205 mm ²	≤ 160 mm ²	Full range
	Slip resistance (wet pendulum test)	AS 4586-2013/ AMDT1-2017	N/A	P3	Matt
	Chemical resistance	EN ISO 10545-13	Min. GB	Class 5	Full range
	Stain resistance	ISO 10545-14	Min class 3	Class 5	Full range
	Origin	N/A	N/A	China	Full range
	Shade variation	N/A	N/A	V3	Full range

Packing Information

Tile description		Quantity per box	Quantity per m2		Quantity per pallet	
Size (mm)	Texture	Pieces	Pieces	Weight	m2	boxes
Sqaure Mosaic	Matt	11	-	1.80kg	-	-
Chevron Mosaic 260x300	Matt	11	-	1.60kg	-	-
50 x 300	Matt	40	66.67	20.00kg	64.80	108
300 x 300	Matt	11	11.11	20.14kg	55.44	56
300 x 600	Matt	8	5.56	22.22kg	57.60	40
600 x 600	Matt Textured	4	2.78	20.50kg	57.60	40
600 x 1200	Matt	2	1.39	22.22kg	46.08	32



The data and information contained in these specification sheets are indicative only unless stated otherwise. As ColorTile cannot control the conditions under which these products are manufactured, the specifications supplied should be considered as suggested guidelines only and are subject to batch variation. The information contained in these specification sheets should not be considered a warranty, expressed or implied, including, but not limited to, a warranty of merchantability or fitness for a particular purpose. To the maximum extent permitted by law, ColorTile will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. No express or implied warranties are given in respect of any specification provided herein other than those that cannot be excluded under the Australian Consumer Law.

Slip ratings are indicative only. Actual performance may vary depending on installation, surface conditions, and maintenance.

Slip Check to AS 4586-2013 Pietra

Report Number: R34242

Report Date: 31 July 2025

Total Number of Pages 2

Safe Environments quality management system is certified to ISO 9001:2015

Accredited for compliance with ISO/IEC 17025 – Testing

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection, proficiency testing scheme providers and reference materials producers reports and certificates

Issued by

Safe Environments Pty Limited
6/7 Inglewood Place
Norwest NSW 2153

Prepared for

Japan Ceramics Pty Ltd
26 Daisy Street
Revesby NSW 2212

Approved by


Ratan Venkatesan
Authorised Signatory

31 July 2025

Test Report No. R34242

Slip Resistance Classification of New Pedestrian Surface Materials

AS 4586-2013 Appendix A (Wet Pendulum Test)

The slip resistance classification has been determined for unused surfaces under specific conditions. Factors such as usage, cleaning systems, applied coatings and patterns of wear may affect the characteristics of the surface after classification. Standards Australia Handbook 198:2014 *Guide to the specification and testing of slip resistance of pedestrian surfaces* provides guidance for the selection of slip resistant pedestrian surfaces classified in accordance with AS 4586-2013. It is recommended that this test report be read in conjunction with AS 4586, HB 197 & HB 198.

Requested by: Japan Ceramics Pty Ltd
Client Address: 26 Daisy Street
Revesby NSW 2212
Product Manufacturer: WenZhou J & F Foreign Trade Co., Ltd
Product Description: Pietra

Test conducted according to: AS 4586:2013 Appendix A
Sampling Procedures: Performed by client and tested as received.
Location: 6/7 Inglewood Place, Norwest NSW 2153

Conducted by: Ratan Venkatesan

Date: 31 July 2025
Sample: Unfixed
Rubber slider used: Slider 96
Slope of specimen: Tested on a flat level surface
Direction of Test: N/A

Temperature: 15°C
Cleaning: None
Conditioned: Grade P 400 paper dry followed by wet lapping film

	Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5
Mean BPN of last 3 swings:	50	51	49	49	50

Reported SRV of Sample:	50
Class:	P4

The expanded uncertainty (U_{95}) at the 95% level of confidence with a coverage factor (k) of 2 has been estimated to be 3 BPN or 8 %, whichever is the greater; sampling uncertainty has not been included. The expanded uncertainty should be considered when interpreting results or assessing conformity. Results relate only to items tested.

Slip ratings are indicative only. Actual performance may vary depending on installation, surface conditions, and maintenance.

Slip Check to AS 4586-2013 Pietra Textured

Report Number: R35511d

Report Date: 1 May 2026

Total Number of Pages 2

Safe Environments quality management system is certified to ISO 9001:2015

Accredited for compliance with ISO/IEC 17025 – Testing

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration, inspection, proficiency testing scheme providers and reference materials producers reports and certificates

Issued by

Safe Environments Pty Limited
6/7 Inglewood Place
Norwest NSW 2153

Prepared for

Japan Ceramics Pty Ltd
26 Daisy Street
Revesby NSW 2212

Approved by



Carl Strautins
Authorised Signatory

1 May 2026

Test Report No. R35511d

Slip Resistance Classification of New Pedestrian Surface Materials

AS 4586-2013 Appendix A (Wet Pendulum Test)

The slip resistance classification has been determined for unused surfaces under specific conditions. Factors such as usage, cleaning systems, applied coatings and patterns of wear may affect the characteristics of the surface after classification. Standards Australia Handbook 198:2014 *Guide to the specification and testing of slip resistance of pedestrian surfaces* provides guidance for the selection of slip resistant pedestrian surfaces classified in accordance with AS 4586-2013. It is recommended that this test report be read in conjunction with AS 4586, HB 197 & HB 198.

Requested by: Japan Ceramics Pty Ltd
Client Address: 26 Daisy Street
Revesby NSW 2212
Product Manufacturer: Wenahou J And F Foreign Trade Co Ltd
Product Description: Pietra Textured

Test conducted according to: AS 4586:2013 Appendix A
Sampling Procedures: Performed by client and tested as received.
Location: 6/7 Inglewood Place, Norwest NSW 2153

Conducted by: Nathan Vanderburg

Date: 30 April 2026
Sample: Unfixed
Rubber slider used: Slider 96
Slope of specimen: Tested on a flat level surface
Direction of Test: N/A

Temperature: 22°C
Cleaning: None
Conditioned: Grade P 400 paper dry followed by wet lapping film

	Specimen 1	Specimen 2	Specimen 3	Specimen 4	Specimen 5
Mean BPN of last 3 swings:	65	65	65	67	67

Reported SRV of Sample:	65
Class:	P5

The expanded uncertainty (U_{95}) at the 95% level of confidence with a coverage factor (k) of 2 has been estimated to be 3 BPN or 8 %, whichever is the greater; sampling uncertainty has not been included. The expanded uncertainty should be considered when interpreting results or assessing conformity. Results relate only to items tested.